

## FL10 SPECIFICATIONS

### OVERALL DIMENSIONS

WIDTH = 32"                      DEPTH = 44" (46" GAS)  
HEIGHT = 82" (84-1/2" GAS)                      HEIGHT WITH DOOR OPEN = 103-1/2"  
DOOR OPENING = 28-3/4" WIDE x 30" HIGH

### HOT WATER SYSTEM

1/2" HOT WATER SUPPLY REQUIRED, UNION PROVIDED  
140° F. WATER REQUIRED AT THE MACHINE  
78 GPH AT 20 PSI (6-1/2 GAL./CYCLE x 12 CYCLES/HR.)  
RINSE BOOSTER: ONE 9 KW HEATING ELEMENT IN A 8-1/2 GAL. RINSE TANK

### FULL LOAD AMPS

	208 VOLT	230 VOLT	460 VOLT
ELECTRIC	71.0	65.2	33.6
GAS/STEAM (INJECTED)	46.0	42.6	22.3
STEAM (RECIRCULATING)	22.0	20.0	11.0

### GAS SYSTEM (GAS MACHINES ONLY)

1/2" GAS SUPPLY  
NATURAL: 6" W.C. MINIMUM INLET, 3-1/2" W.C. MAIN MANIFOLD = 36,000 BTU  
PROPANE: 11" W.C. MINIMUM INLET, 6" W.C. MAIN MANIFOLD = 36,000 BTU  
3" STAINLESS STEEL CHIMNEY ON BACK OF MACHINE

### STEAM SYSTEM (STEAM MODELS ONLY)

3/4" STEAM LINE, 1015 PSI – 18 LBS. PER HOUR AVERAGE - INJECTED  
36 LBS. PER HOUR AVERAGE - RECIRCULATING

### WASH SYSTEM

7-1/2 HP PUMP RECIRCULATES APPROXIMATELY 130 GPM @ 55 PSI

HEAT: >ELECTRIC – ONE 9 KW HEATING ELEMENT  
>GAS – TWO 18,000 BTU RATED INFRARED BURNERS = 36,000 BTU  
>STEAM – DIRECT INJECTION, 10-15 PSI, 18 LBS. PER HOUR AVERAGE  
RECIRCULATED, 10-15 PSI, 36 LBS. PER HOUR AVERAGE

30 GALLON WASH TANK  
1-1/2" COPPER DRAIN  
8" STEAM EXHAUST VENT COMPANION FLANGE