



Lye application
machine
Allround Peelboard

The fastest lye application machine in its class!
- now with peelboard feeding!



BENEFIT

- equal showering results also on high speed because of 2 lye waterfall curtains plus patented WP Riehle lye shower
- the adjustable tankheater avoids the drop down of the lye temperature and guarantees constant shine and colour throughout the entire production time
- computer control for adjustable speed
- speedy control enables new feeding while the previous feed is still on the way
- long shower belt enables showering of large products
- tray deposit belt keeps baking trays clear from excess toppings
- rollable 180 liter
- tank lyelevel sensor prevents pump of running dry

OPTIONS

- automatic scattering unit with brush roller, speed adjustable for different scattering toppings
- exchange toppings container for scattering unit

TECHNISCHE DETAILS

Tray size 580 x 780 mm

Length operational	4.410 mm
Length rest position	3.170 mm
Width	925 mm
Capacity	up to 400 trays per hour
Weight	approx. 400 kg
Voltage	3x230 V/400 V/N/PE/50 Hz
Max. connected load	10 kW/15A
Connector	CEE 32 A
Lye tank capacity	approx. 180 litre

WP LEBENSMITTELTECHNIK RIEHLE GMBH

Heinrich-Rieger-Str. 5 // D-73430 Aalen, Germany // Phone +49 7361 5580-0 // Fax +49 7361 5580-2281
 info@riehle.de // www.wp-riehle.de